



DATASHEET

**KAB-ACES-87214-2400-0500LI**

# KAB-ACES-87214-2400-0500LI



LED Backlight Kabel

ES&S Oliver Reiners e.K. · Gewerbering 2 · 41751 Viersen · GERMANY · [www.esskabel.de](http://www.esskabel.de)  
fon: +49 (0)2162 - 266 18 0 · fax: +49 (0)2162 - 266 18 88 · [info@esskabel.de](mailto:info@esskabel.de)

REV: 1.00 1/3  
Copyright© 2011

**DISCLAIMER:**

In the absence of confirmation by device specification sheets, ES&S Oliver Reiners takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

KAB-ACES-87214-2400-0500LI

DATASHEET

## 1. Functional description

This wiring harness allows a quick and easy connection between a display LED-Backlight with a connector of the ACES 87214 series and any other connector. We supply a connector (24-pin) 87214-2400 with 24 strands and unprocessed on one side. This cable is particularly suited for samples and small series.

Technical Data:

- side 1: 24 pin ACES 87214-2400, R=1.00 mm
- side 2: unprocessed
- strands UL1571, AWG28
- length = 500 mm

Advantage:

- customer specific assembly
- available in various lengths

We also offer the assembly of this conductor as well as the complete ready-for-connection cable in small quantities. Please contact us for further information.

We would be glad to submit you our offer without any obligation.

This cable fits for the following headers: STE-87213-2410, 87213-2411

## 2. Pictures



## 3. Dimension

Size: 500.0 (l) x 27.0 (w) x 2.8 (h) (in mm)

**DISCLAIMER:**

In the absence of confirmation by device specification sheets, ES&S Oliver Reiners takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

