

DATENBLATT

KAB-USB-A-F-USB-A-M-0500SW



BESCHREIBUNG

This cable is designed for the extension of an USB wire and for mounting the female connector to a panel or case. Various lengths are available from stock. A customized version can also be produced.

TECHNICAL SPECIFICATIONS:

- side 1: USB type A female with flange UNC4/40 thread
- side 2: USB type A male
- wire 1P+2C+2B, AWG24+28, black color, l = 500 mm
- [UL 2725](#)
- weight: 35 g

This cable is available in various lengths:

KAB-USB-A-F-USB-A-M-1000SW (l = 1000 mm)

KAB-USB-A-F-USB-A-M-1800SW (l = 1800 mm)

KAB-USB-A-F-USB-A-M-3000SW (l = 3000 mm)

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BILDER

