

DATENBLATT

KAB-HDMI-M-HDMI-F-PANEL-06000RK



BESCHREIBUNG

3ft Standard HDMI® cable for panel mounting.

TECHNICAL SPECIFICATIONS:

- side 1: HDMI male, 19 pin connector
- side 2: HDMI female, 19 pin connector with flange, screw-in, flange = 25 mm
- round cable AWG28, black, PVC - Polyvinyl Chloride, DMG rated, length = 600 mm
- thread length of the screws: 15 mm
- operating temperature: -20 °C to 85 °C
- weight: 51.2 g

Provides a well-secured, easy to access HDMI connection on any processor port or control panel.

Extend your HDMI® interface and allow you screw mount it to a panel.

Panel mount connector for embedded installations.

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BILDER



Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support