

## DATENBLATT

### FFC0.50A50-0146L-2-2-06-06-AU-SC-FH41



## BESCHREIBUNG

This FFC cable type is particularly suitable for the connector series of the manufacturer Hirose FH41 and FH48 (header) due to its punching out, the so-called "side catcher".

## TECHNICAL SPECIFICATIONS:

- Number of wires: 50
- Grid: 0.50 mm (+/- 0.05 mm)
- Cross sections:
- Contact length: 2 mm (+/- 0.5 mm)
- Reinforcement length: 6 mm (+/- 1.50 mm)
- Contact strength in mating area: 0.3 mm (+/- 0.05 mm)
- 80°C, 30 V, AC, VW-1
- Total length: 150 mm
- [UL 2896](#)

FFC cables fit to Hirose connector series:

- [FH41-50S-0.5SH\(05\)](#)
- FH48-50S-0.5SH(05)

This FFC cable is also available in the length:

**78 MM** (FFC0.50A40-0074L-2-2-06-06-AU-SC-FH41)

**350 MM** (FFC0.50A68-0346X-2-2-06-06-AU-SC-FH41)

**798 MM** (FFC0.50A68-0794L-2-2-06-06-AU-SC-FH41)

Fits with the following LCD's: TX31D203VM0EAB

## BILDER



Passender Steckverbinder /  
suitable connector  
Hirose  
STE-FH41-50S-0.5SH(05)

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support