

DATENBLATT

STE-ACES-91209-01011



BESCHREIBUNG

10-pin ACES IDC connector of the series 91209. Used material UL94V-0 matching with AWG32 strands with an outer diameter of 0.52 to 0.56 mm. The minimum order quantity amounts to 1000 pieces.

This wire-to-board connector is normally used for LED backlight cables.

Our matching customized cable assembly is among others [KAB-ACES-91209-01011-0500LI](#). This cable has our standard length of 500 mm.

FURTHER CUSTOMIZED LENGTHS ARE AVAILABLE UPON REQUEST:

- 100 mm - KAB-ACES-91209-01011-0100LI-1:1
- 200 mm - KAB-ACES-91209-01011-0200LI-1:1
- 500 mm - KAB-ACES-91209-01011-0500LI-1:1
- 1000 mm - KAB-ACES-91209-01011-1000LI-1:1

This connector matches with the following pin strips:

- STE-ACES-91208-01001-H01

This connector is i.a. suitable for the following displays:

G104X1-L04, G121X1-L03, G104V1-T03, FG100451DSSWNG01, TX31D45VM, AM-1024768GTMQW-T00H, VGG107603-0TMLWD, VGG107603-0TMLWC, G121XCE-L02

BILDER



Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support