

DATENBLATT

KAB-SET-I-PEX-20453-030-DF13-XXDS-0500LI



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BESCHREIBUNG

Dieses Kabelset bietet Ihnen die Möglichkeit, schnell und einfach eine Verbindung zwischen einem Display mit einem Steckverbinder der Hirose DF13 Serie herzustellen.

Wir liefern Ihnen 30 Einzellitzen mit einem: I-PEX 20453-030 Steckverbinder montiert an Seite 1. Auf Seite 2 sind die bestückten Crimpkontakte DF13-2628SCF ungesteckt, die drei passenden DF13-20DS, -30DS und -40DS Steckergehäuse sind im Lieferumfang enthalten. Somit können Sie ganz einfach, nach Ihren eigenen Kabelplänen die entsprechenden Gehäusekammern bestücken.

TECHNISCHE DATEN:

- Seite 1: I-PEX 20453-030
- Seite 2: DF13-20DS/30DS/40DS-1.25C, ungesteckt
- 30 Einzellitzen AWG28, UL1571, L = 500 mm
- beiliegende Leergehäuse: DF13-20DS, -30DS und 40DS
- Temperaturbereich: -20 °C bis 85 °C
- Gewicht : 17,8 g

VORTEILE AUF EINEN BLICK:

- Mustermengen ab Lager verfügbar
- einseitig individuell selbst bestückbar
- andere Längen lieferbar

Gerne bieten wir Ihnen die Konfektionierung dieser Leitung sowie die Herstellung eines anschlussfertigen Kabels (nach Ihren Kabelplänen, auch beidseitig bestückt) an. Rufen Sie uns einfach an, wir unterbreiten Ihnen gerne ein unverbindliches Angebot.

Steckverbinder: **20453-030E-12** (30 pol.)

Steckverbinder kompatibel zu: JAE HD1P030MA1, TE 5-2069716-2, STARCONN 111B30-1210TA-G3, Hirose KN38-30S-0.5H, CSTAR LS050-W30B-H10-G

Passende Gegenstecker: STM MSAK24025P30 / PK24025P30, FOXCONN GS13301-1110A-7H, JAE HD1S030HA1,

ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

KAB-SET-I-PEX-20453-030-DF13-XXDS-0500LI

STARCONN 111A30-0000RA-G3, I-PEX-20455-030E, UJU IS050-L30B-C10, STARCONN 300E30-0010RA-G3, ACES 50473030

Passend für Displays: HX104X01-212, HV101WX1, FG100180DSSWNG01, B156HW01 V3 , N156BGE-E41, N173HGE-E11, G150XTK01.1, G150XTN03.4, G150XTN03.7, G150XTN03.8, G150XTN06.6, G150XTN06.7, G156HAN02.0, G150XTK02.0, G150XTN06.A, G133HAN02.0, LM238WR2-SPE1, N133HCE-GA1, N116HSE-EBC, NV133FHM-N52, TM116VDSP01-00

Passende Board Steckverbinder: STE-20455-030E-12 (30 pol.)

Passendes Board: C6-AD-T6T2

ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

KAB-SET-I-PEX-20453-030-DF13-XXDS-0500LI

BILDER



ES&S Solutions GmbH
 Gewerbering 2
 41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
 Fax: +49 (0)2162-266-18-88
 E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support