

DATENBLATT

KAB-SET-I-PEX-20453-030-DF13-XXDS-0500LI



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

KAB-SET-I-PEX-20453-030-DF13-XXDS-0500LI

BESCHREIBUNG

This cable set gives you the ability to quickly and easily connect a display to a Hirose DF13 Series connector.

We supply you with 30 single stranded wires with one: I-PEX 20453-030 connector mounted on side 1. On the other side the assembled DF13-2628SCF crimp contacts are unplugged, the three matching DF13-20DS, -30DS and -40DS connector housings are included. Thus you can easily equip according to your own cable plans the corresponding housing chambers.

TECHNICAL SPECIFICATIONS:

- side 1: I-PEX 20453-030
- side 2: DF13-20DS / 30DS / 40DS-1.25C, unplugged
- 30 single stranded wire AWG28, UL1571, L = 500 mm
- attached connector housings: DF13-20DS, -30DS and 40DS
- operating temperature: -20 ° C to 85 ° C
- weight: 17.8 g

ADVANTAGES:

- sample quantities available from stock
- individually self-equipable
- other lengths available

We are happy to offer you the assembly of this cable as well as the production of a ready-to-connect cable (according to your cable diagrams, also equipped on both sides). Just call us – we would be happy to make you a non-binding offer.

Connector: **20453-030E-12** (30-pin)

Series compatible with: JAE HD1P030MA1, TE 5-2069716-2, STARCONN 111B30-1210TA-G3, Hirose KN38-30S-0.5H, CSTAR LS050-W30B-H10-G

Matching connectors: STM MSAK24025P30 / PK24025P30, FOXCONN GS13301-1110A-7H, JAE HD1S030HA1, STARCONN 111A30-0000RA-G3, I-PEX-20455-030E, UJU IS050-L30B-C10, STARCONN 300E30-0010RA-G3, ACES

ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

KAB-SET-I-PEX-20453-030-DF13-XXDS-0500LI

50473030

Fits for displays: HX104X01-212, HV101WX1, FG100180DSSWNG01, B156HW01 V3, N156BGE-E41, N173HGE-E11, G150XTK01.1, G150XTN03.4, G150XTN03.7, G150XTN03.8, G150XTN06.6, G150XTN06.7, G156HAN02.0, G150XTK02.0, G150XTN06.A, G133HAN02.0, LM238WR2-SPE1, N133HCE-GA1, N116HSE-EBC, NV133FHM-N52

Matching board connectors: STE-20455-030E-12 (30-pin)

Fits to board: C6-AD-T6T2

ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

KAB-SET-I-PEX-20453-030-DF13-XXDS-0500LI

BILDER



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support