

**DATENBLATT**

**KAB-IP67-VM-MICRO-B-F-MICRO-B-M-0100RK-M12**



## BESCHREIBUNG

We are very proud of our new IP67-baby!  
It is small but powerful!

We offer the small Mirco USB panel socket in a nickel-plated brass version. Also included are a dust cap with wire loop that protects the adapter from dust and dirt, and a nut that firmly mounts the socket in your device.

The adapter, with its high-quality housing, is specifically adjusted to the needs of industrial applications. With its screw-on sealing cap and internal seal, the adapter reaches the IP67 protection class.

## TECHNICAL SPECIFICATIONS:

- side 1: IP67 USB micro type B, female, fully occupied, nickel-plated brass
- side 2: USB micro type B, male, fully occupied
- round cable: USB 2.0 cable, black
- AWG28, UL2725, 80 °C, 30 V
- L = 100 mm (inside)
- screw connection: nut smooth, M12
- protective cap with internal seal and wire loop, aluminium

Learn more about the general [IP PROTECTION CLASSES](#).

BILDER



Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support