

DATENBLATT

KAB-IP67-VM-USB-A-M-USB-A-M-2000RK-M20-S



BESCHREIBUNG

This IP67 USB 2.0 solution is our successor model to the following article: KAB-IP67-VM-USB-A-M-USB-A-M-1000RK-M20 - now with much shorter body!

The IP67 connector offers, with its union nut, a secure screw connection. The connector is with the appropriate counterpart absolutely dust- and waterproof and complies with the IP67 protection class. The stable IP67 socket is of high quality and particularly robust due to the metal housing. This makes it ideal for all installations and applications in industrial environments. Especially in harsh industrial environments, reliable data transmission is essential, which defies dust, dirt and water. The high-quality workmanship is a guarantee for continuously running production processes.

The standard cable length is 2000 mm. We can manufacture other lengths, even in small quantities, for you at any time!

Technical specification:

- side 1: IP67 USB 2.0 Type A, male, screwable, suitable for female version M20, full metal
- side 2: USB 2.0 Type A, male
- round cable: USB 2.0, UL2725, (80 °C, 30 V), beige
- L = 2000 mm
- weight: 105 g

Discover more of our precise, fully assembled IP67 solutions or assemble your individual connectors with the appropriate components. Talk to us about the special requirements of your application or get additional information about the general [IP protection classes](#). We will be happy to help you and submit an individual offer at any time.

[You will find further accessories under the category IP67 accessories.](#)

BILDER



Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support