

## DATENBLATT

# KAB-IP67-VM-USB-C-M-USB-C-M-1000RK-M12



ES&S Solutions GmbH  
Gewerbering 2  
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0  
Fax: +49 (0)2162-266-18-88  
E-Mail: [info@esskabel.de](mailto:info@esskabel.de)

[www.esskabel.de](http://www.esskabel.de)

**Disclaimer:** In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

## KAB-IP67-VM-USB-C-M-USB-C-M-1000RK-M12

**BESCHREIBUNG**

This article is a USB 3.1 cable with a male IP67 USB 3.1 type C connector on one side and a male USB 3.1 type C connector on the other.

The IP67 USB 3.1 type C connector has a screwable union nut with an M12 thread, thus ensuring a secure connection between the socket and your housing. The plug is dust and waterproof and meets the IP67 protection class when used with the appropriate through socket. You can use the USB 3.1 cable accordingly for all installations and applications in industrial environments.

We can offer you the suitable socket [STE-IP67-USB-C-F-USB-C-F-PANEL](#) , which you can order separately.

**Technical specifications:**

- side 1: IP67 USB 3.1, type C, male, with union nut (nickel-plated brass)
- side 2: USB 3.1, Type C, male
- round cable: USB 3.0, AWG28, black
- L = 1000 mm
- UL2725, (80 °C, 30 V)
- weight: 36,8 g

We can offer this article with customer-specific cable lengths on request. In addition, the article is available in two other standard lengths, 200 mm and 300 mm.

You can order the articles under the following order number:

KAB-IP67-VM-USB-C-M-USB-C-M-2000RK-M12 -> 200 mm

KAB-IP67-VM-USB-C-M-USB-C-M-0300RK-M12 -> 300 mm

In addition, you can also choose a USB A plug variant on the second side. Further IP67 solutions can be assembled for you at any time. Talk to us about the special requirements of your application or find out more about the general [IP protection classes](#). We will be pleased to submit you an individual offer. You will find further accessories under the category [IP67 accessories](#).

ES&S Solutions GmbH  
Gewerbering 2  
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0  
Fax: +49 (0)2162-266-18-88  
E-Mail: [info@esskabel.de](mailto:info@esskabel.de)

[www.esskabel.de](http://www.esskabel.de)

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

## KAB-IP67-VM-USB-C-M-USB-C-M-1000RK-M12

## BILDER



ES&S Solutions GmbH  
 Gewerbering 2  
 41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0  
 Fax: +49 (0)2162-266-18-88  
 E-Mail: info@esskabel.de

[www.esskabel.de](http://www.esskabel.de)

**Disclaimer:** In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support