

DATENBLATT

KAB-CI1606SL00A-NH-0500LI



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BESCHREIBUNG

Bei unserer LED Inverter Kabelkonfektion wurde der CI16 Steckverbinder von [CVILUX](#) verwendet. Das LED Inverter Kabel ist für Wire-to-Board-Verbindungen konzipiert und für Backlight Display Anwendungen geeignet.

Hier bieten wir den CVILUX CI16 Stecker in einer sechs poligen Variante im 1.0 mm Raster (Type 1) an. Die zweite Seite ist unkonfektioniert, die AWG28 Litzen sind glatt abgeschnitten. Weitere Polzahlen sind jederzeit verfügbar. Darüber hinaus können wir Ihnen auch kundenspezifische Lösungen anbieten, beispielsweise mit einer Plug-and-Play Version des Steckverbinders. Fragen Sie uns unverbindlich, wir beraten Sie gerne hierzu!

Technische Daten:

- Seite 1: 6pol. CVILUX CI1606SL00A-NH
- Seite 2: glatt abgeschnitten, unbestückt
- Litze: AWG28, UL1571, sw, ws
- L = 500 mm
- Steckzyklen: 2 bis 20
- halogenfrei
- RoHS konform
- bleifreier Verarbeitungsprozess
- Temperaturbereich: -25 °C bis 85 °C
- Gewicht: 4,35 g

Elektrische Eigenschaften:

- Nennspannung: 125 V AC/DC
- Kontaktwiderstand: max. 20 m Ω
- Isolationswiderstand: min.100 M Ω
- Spannungsfestigkeit: 500 V AC für 1 Minute

Passt zu: CI1606M1VR0-NH, CI1606MH1VR0-NH, CI1606M1VRA-NH, CI1606MH1VRA

ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BILDER



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support