

DATENBLATT

ADA-COMPACTFLASH-SATA-REV-1



BESCHREIBUNG

Convert CompactFlash to SlimLine low power 2.5" SATA HDD!

This adapter is a small compact flash memory card adapter designed to replace a 2.5"S-ATA/SATA hard drive.

TECHNICAL SPECIFICATIONS:

- extremely small dimensions
- 22 pin SATA (signals and power)male connector on board
- Supports CompactFlashTM cards (type I & II) or a IBM MicrodriveTM
- Transparent to the operating system, no drivers required
- The CF card can be utilized as a primary bootable device containing the OS and application.
- The shock resistance and the extremely low power consumption is comparable to a SSD drive.
- RoHS compliant
- dimension: 74 (l) x 51 (w) x 6 (h) (in mm)
- operating temperature: 0.01 °C to 70 °C
- weight: 16.2 g

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BILDER



Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support