

DATENBLATT

ADA-USB-PANEL-HUB-4-PORT-REV-01



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BESCHREIBUNG

Aktiver USB-HUB speziell für industrielle Applikationen entwickelt zur Umwandlung von einem USB Anschluß zu 4 USB 2.0 Anschlüssen.

Dieser USB HUB ist speziell für industrielle Anwendungen entwickelt und hat ein unempfindliches Alu-Druckguß Gehäuse.

DIESER HUB UNTERLIEGT KEINEN SCHWANKUNGEN IN QUALITÄT, MATERIAL ODER DER REVISION, WIE DAS IN DER PC WELT ÜBLICH IST. Dies unterscheidet unsere Entwicklung wesentlich von anderen USB Adaptern.

TECHNISCHE DATEN:

- Datenübertragungsrate bis zu 480 Mbit/s
- entspricht der Spezifikation für USB2.0 (USB 1.1 abwärts kompatibel!)
- einfachste Installation durch Plug and Play
- PC und MAC kompatibel
- 5V DC Hohlstecker 2.1 x 5.5 mm mit einer Länge von 10 mm
- Abmessung: 50 (L) x 55 (B) x 25 (H) (in mm)
- Temperaturbereich: -20 °C bis 85 °C
- Gewicht : 69,2 g

Im Lieferumfang enthalten ist ein 1 Meter langes USB Kabel mit einem beidseitigen, male Typ A Stecker. Sie würden gerne ein anderes Kabel verwenden? Dann sollte die maximale nutzbare Kabellänge 5 Meter nicht überschreiten. Eine 5V DC Stromanschlussbuchse für das optionale Netzteil ist vorhanden.

ACHTUNG:&NBSP;Ein Netzteil gehört nicht zu unserem Lieferumfang und kann über uns nicht bezogen werden!

Es sind jederzeit kundenspezifische HUB Varianten möglich.

ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BILDER



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment. -Medical equipment for life support