

DATENBLATT

ADA-DF9-31S-FFC31-15



BESCHREIBUNG

This adapter will connect a 31-pin plug or receptacle of Hirose DF9-31S to a 31-pin FFC cable connector with pitch 0.50 mm.

TECHNICAL SPECIFICATIONS:

- side 1: 31-pin SMD connector DF9-31S (15 pin at the outer edge of the adapter)
- side 2: 31-pin FFC connector STE-VI-FPC05P-H09-31-S-2-R-L (Hirose DF12 compatible) bottom contact
- suitable FFC-cables can be ordered separately.
- dimension: 22.5 (l) x 6.5 (w) x 6.67 (h) (in mm)
- operating temperature: -20 °C to 85 °C
- weight: 3.86 g

ADVANTAGES:

- light weight
- approved quality
- different types available on request. For example with connector type DF9-31P which commonly used as an adapter extension.
- FFC cables in different length available ex stock. Please use the [FFC-configurator](#) for your request.

Customized versions of this type can be manufactured on request.

More information you find here: [EDC TO 0.50 MM FFC](#)

BILDER



Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support