

DATENBLATT

ADA-TOUCH-4P-100



BESCHREIBUNG

This adapter is designed to connect a touch controller up to 4 pins to a standard FFC cable with a pitch of 1.00 mm. On side 2 strands, flat- or round-cables can be soldered.

Connections:

- Side 1: FFC connector 4pin, pitch =1.00 mm, ZIF
- Side 2: 4 solder pads with pitch 2.54mm

The suitable FFC cable in various lengths, can be supplied from stock.

Supports the follow Touch or LCD´s:
LT104AC36000

DIMENSIONS

- Länge / Length: 19,0 mm
- Breite / Width: 12,0 mm
- Höhe / Height: 4,5 mm

RANGE OF TEMPERATURES

- Betriebstemperatur / Operating temperature: Min: -20,00 °C Max: 85,00 °C
- Lagertemperatur / storage temperature: Min: -40,00 °C Max: 85,00 °C

WEIGHT

- Bruttogewicht / Gross weight: 2,5 g
- Nettogewicht / Net weight: 1,0 g

BILDER



Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support