

DATENBLATT

KAB-SET-DF9-31S(16)-2002-XX-0500LI



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BESCHREIBUNG

This cable set is designed for a quick and easy connection between a display with a connector of the Hirose DF9 series and any other connector of a graphics board (double rowed with grid = 2 m).

We supply 31 strands with an already mounted DF9-31S-V connector on side 1. The second side is unplugged, it only has assembled crimp contacts including two matching 2002-2x22P housings.

Thus you can assemble the contacts in the housings according to your cable layouts and obtain an optimum function to the signal structures.

This cable is especially suited for the prototype construction, samples and very small quantities.

TECHNICAL SPECIFICATIONS:

- side 1: DF9-31S-1V(16), embedded, unplugged
- side 2: 2002 25x2 pin/22x2 pin grid 2.00 mm, double rowed, unplugged
- 31-pin strands AWG28, UL1571, length = 500 mm
- housings included: STE-2002-2x22P and STE-2002-2x25P
- operating temperature: -20 °C to 85 °C
- weight: 22 g

ADVANTAGES:

- small quantities available from stock
- individual assembling on one side by customer possible
- various lengths available
- this cable will be supplied unplugged with two alternatively matching housings

We also offer the assembling of this cable as well as the manufacturing of a cable ready-for-connection (according to your cable layouts). Please contact us. We will be pleased to submit you our non-binding offer.

This cable is suitable for the following pin headers:

STE-2002-2X22P, STE-2002-2X25P, DF9B-31P-1V, DF9A-31P-1V, DF9C-31P-1V, DF9-31P-1V, DF9MA-31P-1V

ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

KAB-SET-DF9-31S(16)-2002-XX-0500LI

This cable supports the following displays:

AA065VB01, AA084VC02, AA084VC043, AA084VC05, AA104VC01, AA104VC02, LQ064V3DG01, LQ065T9DR51, LQ065T9DR53U, LQ065T9DZ03, LQ084V1DG21, LQ104V1DC31, LQ104V1DG11, LQ104V1DG21, LQ104V1DG51, LQ104V1DG52, LQ104V1DG61, LQ104V1DW02, LQ10D368, LQ10D421, LQ64D343, LTM10C209A, LTM10C210, NL4823BC37-05, NL6448AC33-46, NL6448BC20-08E, NL6448BC20-14, NL6448BC20-20, NL6448BC26-01, NL6448BC26-03, NL6448BC26-09, NL6448BC26-09C, NL6448BC26-22F, NL6448BC33-31, NL6448BC33-46, NL6448BC33-50, NL6448BC33-53, NL6448BC33-54, NL6448BC33-59, NL6448BC33-64, NL6448BC33-64C, NL6448BC33-74, PD064VT1, PD064VT4, PD064VT5, PD104VT1, T-51513D104JU-FW-A-AC, T-51513D104U-FW-A-AB, T-51638D084-FW-A-AA, T-51638D084J-FW-A-AA, T-51638D084J-FW-A-AC, T-51639D084JU-FW-A-AB, T-51639D084U-FW-A-AA, T-51750GD065J-FW-A-AA, T-51750GD065J-FW-AB, V16C6448AC, LQ104V1DG62, TX17D01VM2CAA, G104V1-T03, TX17D01VM2EAB, TCG104VG2AA-G00, G104V1-T03, NL6448BC33-70F

ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BILDER



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support