

DATENBLATT

KAB-DF19G-30S-0500RK



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BESCHREIBUNG

This wiring harness allows a quick and easy connection between a display with a connector of the HIROSE DF-19 series and a graphics board. We supply a twisted pair round cable with 30 assembled crimp contacts and a suitable connector housing. The second side is unprocessed. The connectors can be assembled easily according to your cable layouts to achieve an optimum function and allocation of the pairs to the signal structures. This cable is suited for samples and very small series.

TECHNICAL SPECIFICATIONS:

- side 1: mounted contacts typ DF19A-2830CFA for connector Hirose DF19G-30S-1C, unstucked, enclose
- side 2: unprocessed, just cut off
- Roundcable, AWG28, twin stranded, shielded, UL 20276, OKI, l = 500 mm
- operating temperature: -20 °C to 85 °C
- weight: 35.2 g

ADVANTAGES:

- individual assembling possible
- different lengths available on short notice
- shielded
- with twisted pair
- suitable for LVDS and DVI
- **This cable will be delivered unplugged including connector housing (see fig.).**

We can also offer the assembly of this harness as well as the complete ready-for-connection wiring harness as samples. Please contact us for any information. We would be pleased to submit you our non-binding offer.

This cable fits to the following pin headers:

DF19G-30P-1H, DF19K-30P-1H, DF19L-30P-1H, DF19KR-30P-1H, DF19-30P-1V, GT100-30P-LS-SMT, CNT245-30221, CNT245-30211, MSB24013P30, IP100-C30O-C15, 20268-030E, HS89300, HS90300, IP100-C30O-C15, 20268-030E, P24013P30, MSB24013P30HA, MSB24013P30A, 20230-030B-F, 20230-T30-F, 20230-W30B-F, 107A30-0021RA-G3-R, 20268-030E-12E, CP100-S30G-H16

This following displays will be supported:

ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

LQ084S3DG01, LTM084P363, LTM08C351, LTM08C351S, NL10260BC19-01D, NL160120AC27-22B,
NL160120AM27-13A, NL160120BC27-02, NL160120BC27-10, NL160120BC27-14, NL160120BM27-03,
NL160120BM27-03A, NL12876AC18-03, AM-1024768TTMQW-00H, G133HAN01.0, VGG804818-6UFLWM,
VGG106002-6UFLWH, VGG128004-5TSLWG, VGG128004-5TSLWH, VGG128004-5TSLWI, VGG106002-6UFLWE,
NL160120AC27-32, NL192108AC10-01D

ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BILDER



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support