

DATENBLATT

KAB-SET-DF14-20S-DF13-XXDS-0500RK



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BESCHREIBUNG

Dieser Kabelsatz bietet Ihnen die Möglichkeit, schnell und einfach eine Verbindung zwischen einem Display mit einem STM Steckverbinder DF14-20S-1.25C und einem beliebigen Grafikboardsteckverbinder der Serie STM DF13 in 20-, 30-, oder 40-pol. herzustellen.

Wir liefern Ihnen ein 20 poliges Rundkabel mit einem STM Steckverbinder DF14-20S-1.25C für Seite 1.
Für Seite 3 liegen drei STM Steckverbinder DF13-20DS-1.25C, DF13-30DS-1.25C, DF13-40DS-1.25C bei. Das Rundkabel hat beidseitig montierte Crimpkontakte und wird ungesteckt geliefert.

Sie können dann ganz einfach nach Ihren eigenen Kabelplänen die Kontakte in die entsprechenden Gehäusekammern bestücken und so eine optimale Funktion und Zuweisung der Paare zu den Signalstrukturen erzielen.

Dieses Kabel ist besonders für den Prototypenbau, Muster und Kleinstserien geeignet.

TECHNISCHE DATEN:

- Seite 1: DF14-20S-1.25C
- Seite 2: DF13-20DS-1.25C, DF13-30DS-1.25C, DF13-40DS-1.25C
- beide Seiten sind ungesteckt, 20 polig, hochflexibles Rundkabel, paarig verseilt, UL2560, AWG28, abgeschirmt, L = 500 mm
- Temperaturbereich: -20 °C bis 85 °C
- Gewicht : 31,9 g

VORTEILE AUF EINEN BLICK:

- Mustermengen ab Lager verfügbar
- beidseitig individuell bestückbar
- andere Längen auf Anfrage lieferbar
- abgeschirmt
- mit Twisted Pair
- für LVDS geeignet
- Dieses Kabel wird beidseitig ungesteckt mit passenden Buchsen angeliefert!

Die Konfektionierung dieser Leitung sowie die Herstellung eines anschlussfertigen Kabels (einseitig oder beidseitig nach

KAB-SET-DF14-20S-DF13-XXDS-0500RK

Ihren Kabelplänen bspw.) bieten wir ebenfalls an. Rufen Sie uns an, wir unterbreiten Ihnen gerne ein unverbindliches Angebot.

Dieses Kabel passt zu nachfolgenden Stiftleisten:

DF14-20P-1.25H, MSB240420, MSB240420-E, P240420, GT123-20P-H16, GT123-20S-CS, 3804-F20N-06R, CWY20G-A0D1T, 3804K-F20N-10L, CID520D

Folgende Displays werden unterstützt:

AA150XN01, AA150XN02, G150XG01, G150XG02, G150XG03, LB150X02, LB150X06, LC150X01, LC150X01-A3, LC150X01-SL01, LC150X02, LC150X02-A4, LC150X02-TL01, LC151X01-C3, LC171W03, LC171W03-A4, LC171W03-C4, LC230W01, LC230W01-A2, LC260W01, LC260W01-A5K1, LM150X08, LQ150X1LG45, LQ150X1LG55, LQ150X1LGB1, LQ150X1LGN2, LQ150X1LGN2A, LQ150X1LGN2E, LQ150X1LW71N, LQ150X1LW72, LTM150XH, LTM150XH-L01, LTM150XO-L01, M150XN07, M170XW01, NL10276BC30-17, NL10276BC30-18, NL10276BC30-18C, NL10276BC30-32D, NL10276BC30-33D, NL128102AC31-02, NL12876BC26-25, T140VN01, T201VN02V0, T-51863D150J-FW-A-AA, T-51863D150J-FW-A-AB, T-51863D150J-FW-A-AD, T-51863D150J-FW-A-AE, G150X1, G121SN01, G121SN01V1, G121SN01V2, G121SN01V3, G150XG03V2, G121SN01V4, NL10276BC30-33D, LQ150X1LW71N, LQ150X1LG82, G150XG02V1, T-55519D150J-LW-A-AAN, G121SN01-V4, NL10276BC30-34D, HT15X15, G121NX01, G150XG01 V3, LQ150X1LG91, SCF0700720GGU12, FG0700K6DSSWBG01, G150XTN05.1, CLAA150XP01Q, CLAA150XP07FQ, CLAA150XP07Q, AC150XA01, AC150XP01, CLAA150XP04, CLAA150XP01PQ, CLAA150XP01PE, LQ150X1LG76, CLAA150XP06 CW, CLAA150XP07 CW, CLAA150XP07Q, CLAA150XP07FQ, G150XG03 V0, G150XG03 V1, M150EW02 V0, M150XN07 V2, M150XN07 V3, MI700J1T-2, G150XNE-L01, G150XNE-L03, T150NB02D01, OT070KGDWLL, OT070PGDDLT-H0, OT070PGDDLT-H1, OT080FSDDL-V0, OT090AGDDLT-00, OT101CAWDLT-00, OT101DAWDLV-H0, LQ101K1LY05, OT104ASDDL-V0, G121SN01 V402, G121SN01 V403, G121STN01.0, G121XTN01.0, OT121AXWDLV-H0, LQ121K1LG52, LQ121K1LG53, LQ123K3LG01, G150XAN01.1, G150XTK01.0, G150XTN03.2, G150XTN06.2, G150XTN06.3, G150XTN06.4, G150XTN06.8, G150XTN06.9, OT150CXDDL-V0, OT150ZXUDLV-00, LQ150X1LW95, LQ150X1LW96, LQ150X1LX95, LQ150X1LX96, LQ150X1LX9A, LQ201U1LW31, LQ201U1LW32, G215HAN01.0, G215HVN01.1, JH215WLPNN, LM215WF3-SLC1, LM215WF3-SLK1, LM215WF3-SLN1, OT215BFWDLV-00, OT215ZFWDBL-00, NL12876BC26-32D, G150XAN01.2, G150XTK02.0, G150XTN06.A, G121XN01 V001, G121XN01 V0, NL13676BC25-03F, LQ121K1LG52U, NL13676AC25-05D, TM150TDSG71, NL10276AC30-52C, NL13676BC25-07F, G150XGE-L06, LQ150X1LW12, TM121SDS01, TM121TDSG02, G150XGE-L04, PH102768T-001, G150XGE-L07, NL10276AC30-48D, G150XTN03.0, NL13676BC25-03F, LQ121K1LG52U, NL13676AC25-05D, G150XAN02.1, HM150X01-N01, NLB121SV01L-01, NLB121XG01L-01, NL10276BC30-39, NLB150XG01L-01, G150XAN01.0

Folgende Boards werden unterstützt:

?PICO-BT01, D3544

ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BILDER



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support