

DATENBLATT

KAB-FI-RE51-0350FFC



BESCHREIBUNG

This cable set allows a quick and easy connection between a display with a connector of the FI-R series and a graphics board connector of the same series. The special mechanical locking system ensures a tight fit in this application. Thus this cable is perfectly suitable for robust applications. We supply a FFC cable with a shield of aluminium and 2 identical connectors compatible with FI-R series on both sides.

TECHNICAL SPECIFICATIONS:

- side 1: FI-RE51 gold plated, with special mechanical locking, grid = 0,50 mm
- side 2: FI-RE51 gold plated, with special mechanical locking, grid = 0,50 mm
- FFC cable with aluminium shielding on one side
- **configuration 1:51**
- contact resistance: max. 40 M ohm
- EMI controlling (electromagnetic interference) due to a protective layer on the FFC and a metal shell on the connector.
- operating temperature -40°C ~ +80°C, UL2896
- L = 370 mm (outer diameter, connector to connector)
- suitable for the latest generation of high speed transmissions

This cable fits with the following headers:

FI-RE51S-HF, FI-RE51S-HF-J-R150, FI-RE51S-HF-R1500, FI-RE51S-HF-SS-R1500, FI-RE51S-HFA-R1500, FI-RE51S-VF-J-R130, FI-RE51CL, FI-RE51CLS, FI-RE51HJ, FI-RE51-FTS, GT05L-51S-H38, 187059-51221, MSAKS24020P51, IS050-C51B-C39-A, FI-RTE51SZ-HF, 115E51-0000RA -M3-R

This cable fits with the following housings:

PKS24020P51, kompatibel zu JAE FI-RE Serie

The following displays will be supported:

LC420WU1, LC470WU1, LTI520HB01, LTI570HH, LTI570HH-L01, LTI700HD01, LTI820HT, NL192120AC25-02, T370HW01, T370HW02, T370XW02, T420HW01, T420HW02V0, LTI400HA03, LTA320HA02-001, LTA400HA07, LTA460HB07, LTI520HB01, LTI570HH-L01, LTI570HH-L01, V420H1, V470H1, V562D1, V570H1, V520H1, LD520WU1, LD420WUB, LC370WUN, LK315D3LA17, LK315D3LZ73Y, LK370T3LZ7KZ, LK400D3LA33, LK400D3LA43, LK420D3LA4, LK460D3LA43, LK520D3LA13, LK520D3LA53, LK520D3LA63, LK520D3LA73, LK520D3LZ13,

LK520D3LZ33, LK558Z3LA1P, LTI400HA02, LTI460HA02, LTI550HF02, LK520D3LZ89, V470H1-L03, P645HW04V0, T260HW02V1, P650HVN01, LD320EUN-SEM1, LC260EUN-SCA1, P280HVN01.0, LTI400HA10, LC32DUE-SFR1, LTI480HN01, LM238WR2-SLA1, LM238WR2-SLC1, G240UAN01.0, G240UAN01.1, LM265SQ1-SLA1, G270ZAN01.0, G270ZAN01.1, G286HAN01.0, LM290WW2-SSA1, LM310UH1-SLA2, LQ315D1JG93, LQ315D1VG01, LD320EUN-SEM1, LD320DUE-FHB1, G320ZAN01.0, SL3228ML-L1A, SL3229ML-L3, LD420EUB-SDA1, LD420EUN-UHA1, SL4238ML-HGB, LD430EUE-FHB1, LTI370LN03-V, P420IVN01.0, S290AJ1-LE1, P370IVN02.0, P420HVN02.1, LTI750HF01-V0, P290IAN01.0, P430HVN01.1, P550HVN03.2, P650HVN04.0, S290AJ1-LE1, S290AJ1-LE2, P460HVN03.1, M315DJJ-K30, P420HVN03.1, P650HVN03.0, P650HVN05.1, P320HVN04.1, S400DJ1-KS5_V1, S580DJ2-KS5, S750DK1-K02, P460HVN04.3, LD420EUN-UHA3, M315DJJ-K31, P370IVN03.0, S500DJ2-KS5, LTI460HF01-V, S400HJ6-LE8_C2, P550QVF06.0, M280DGJ-L30, P320HVN02.0, S500HJ1-LE8, P420HVN02.1, LTI750HF01-V0, LTI550HF04, P650QVF03.0, LD320EUN-SLM1, LD550EUN-UHA3, S290AJ1-LE2, P460HVN02.1, P370IVN01.0, S290AJ1-LE2, P460HVN03.1, P420HVN03.1, P550HVN06.0, P650QVF02.0, P320HVN07.0, LD750DGN, LD490EUE, P485IVN01.0, LB315WRM, P370IVN04.0

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BILDER



Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support