

DATENBLATT

KAB-FI-W15S-0500RK



BESCHREIBUNG

This wiring harness allows a quick and easy connection between a display with a connector of the FI-W series and a graphics board. We supply a twisted pair round cable with 31 assembled crimp contacts and a suitable connector housing. The second side of the cable is unmachined. The connectors according to your cable plans can easily be assembled to achieve an optimum function and allocation of the pairs to the signal structures. The cable is especially suited for samples and very small series.

ADVANTAGES:

- individual assembling possible
- different lengths available on short notice
- shielded
- with twisted pair
- suitable for LVDS and DVI
- **this cable will be supplied unplugged including connector housing!**

TECHNICAL SPECIFICATIONS:

- side 1: mounted contacts typ FI-C3-A1-15000 for connector FI-W15S, p = 1.25 mm, unplugged enclosure
- side 2: unprocessed, just cut off
- round cable LTG-DCY-08X2X0,09 mm, 16-pin, shielded, grey, AWG28
- **UL 2560**

This cable is available in black, halogen-free and in various lengths.

We can also offer samples of the complete assembled ready-to-use wiring harness. We would be pleased to submit you our non-binding offer.

This cable fits to the following pin headers:

- FI-W15P-HFE
- FI-W15P-HF
- FMWA1214A-15A

Cable assembly is compatible for:

- 679489-02
- 679489-04
- 606544-02
- 606544-04

The following electrical appliances or displays will be supported:

- Renco - Drehgeber R35i

BILDER

