

## DATENBLATT

# KAB-BHSMR02-0500LI



ES&S Solutions GmbH  
Gewerbering 2  
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0  
Fax: +49 (0)2162-266-18-88  
E-Mail: [info@esskabel.de](mailto:info@esskabel.de)

[www.esskabel.de](http://www.esskabel.de)

**Disclaimer:** In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

## BESCHREIBUNG

This wiring harness is designed for a quick and easy connection between a LED-backlight display with a connector of the JST BHSR series and any other connector. We supply a 2-pin connector BHSMR-02V-S assembled with 2 strands and a socket housing. The second side of the cable is unprocessed. This cable is particularly suited for samples and small series.

## TECHNICAL SPECIFICATIONS:

- side 1: BHSMR-02V-S with crimp contact SBHSM-002T-P0.5
- side 2: unprocessed
- strand: white + red, AWG26, UL1061, l = 500 mm
- pin 1 = red
- pin 2 = white
- dimension: 500 (l) x 7.6 (w) x 3.8 (h) (in mm)
- operating temperature: -20 °C to 85 °C
- weight: 3.8 g

## ADVANTAGES:

- available ex stock
- customer specific assembly
- deliverable in different lengths within a short term

We also offer the assembly of this harness as well as the complete cable ready-for –connection in small quantities. Please contact us for any information. We would be glad to submit you our offer without any obligation.

This cable fits for the following pin headers:

- BHSR-02VS-1
- 35001HS-02

The following LCDs or inverter will be supported:

LTM190M2-L31, SX19V007, SX21V00, PD080SL2, VGG804808-6UFLWC Rev. 3,

BILDER



ES&S Solutions GmbH  
Gewerbering 2  
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0  
Fax: +49 (0)2162-266-18-88  
E-Mail: info@esskabel.de

[www.esskabel.de](http://www.esskabel.de)

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support