

DATENBLATT

KAB-GHR-08V-S-0500LI



BESCHREIBUNG

This wiring harness allows a quick and easy connection between a LED backlight display with a JST connector of the GH series and any other connector. We supply an 8-pin flexible wire with assembled socket housing. The second side of the cable is unprocessed. This cable is particularly suited for samples and small series.

TECHNICAL SPECIFICATIONS:

- side 1: GHR-08V-S
- side 2: unprocessed
- 8 x black wire, AWG28, L = 500 mm
- [UL iQ™1061](#)

ADVANTAGES:

- available ex stock
- customer specific assembly
- deliverable in different lengths on short notice

We also offer the assembly of this conductor as well as the complete cable ready-for-connection in small quantities. Please contact us for any information. We would be glad to submit you our offer without any obligation.

It supports the following displays and devices:

G190ETN01.2_REV0.0, G190ETN01.4

BILDER



Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support