

DATENBLATT

KAB-ACES-50204-40-0500LI



BESCHREIBUNG

This wiring harness allows a quick and easy connection between a display with a connector of the ACES 50204 series and any other connector. We supply a connector (40-pin) 50204 with 40 strands and an assembled socket housing on one side. This cable is particularly suited for samples and small series.

TECHNICAL SPECIFICATIONS:

- side 1: 40-pin ACES 50204-40, p = 0.50 mm
- side 2: unprocessed, just cut off
- strands AWG32, black and white
- length 500 mm
- [UL iQ™10064](#)
- operating temperature: -10 °C to 85 °C
- weight: 10.4 g

ADVANTAGES:

- available ex stock
- customer specific assembly
- available in various lengths
- available in various versions for example Micro-Coax, round cable [KAB-ACES-50204-40-0300COAX-RK](#)

We also offer the assembly of this conductor as well as the complete ready-for-connection cable in small quantities. Please contact us for further information. We would be glad to submit you our offer without any obligation.

This cable fits for the following header:

[STE-ACES-50203-040-0-N-001](#), Starconn 107F40

This cable fits for our adapter set:

[ADA-ACES-50204-40-SET](#)

This cable is suitable for Intel® Desktop Board: DH61AG, DN2800MT

This cable is suitable for onga-IC87, Conga-IC97 Thin Mini-ITX SBC

BILDER

