

DATENBLATT

KAB-87439-0500-0500LI



BESCHREIBUNG

This cable is designed for a quick and easy connection between a LED-backlight display with a Molex connector of the Pico-Spox™ 87439 series and any other graphic board connector.

TECHNICAL SPECIFICATIONS:

- side 1: 87439-0500, matching crimp contact 87421-0000
- side 2: open end, just cut off
- 5 x Litze AWG24, white
- L = 500 mm
- UL1061
- operating temperature: -20 °C to 85 °C
- weight: 7.5 g

ADVANTAGE:

- available ex stock
- customer specific assembly
- available in different lengths

We also offer the assembly of this conductor as well as the complete cable ready-for-connection in small quantities. Please contact us for any information. We would be glad to submit you our offer without any obligation.

BILDER



Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support