

## DATENBLATT

### KAB-SHLP-08-0500LI



## BESCHREIBUNG

This wiring harness allows a quick and easy connection between a LED-display inverter with a connector of the JST SHLP series and any other graphic board connector. We supply a 8-pin connector SHLP-08V-S-B assembled with 8 strands and a socket housing. The second side of the cable is unprocessed. This cable is particularly suited for samples and small series.

## TECHNICAL SPECIFICATIONS:&NBSP;

- side 1: 8-pin JST SHLP-08V-S-B, R = 1.00 mm with crimpcontact SSSL-003T-P0.2
- side 2: unprocessed
- AWG28
- L = 500 mm
- strands in black
- [ULiQ™1571](#)
- operating temperature: -20 °C to 85 °C
- weight: 4.6 g

## ADVANTAGES:&NBSP;

- available ex stock
- customer specific assembly
- deliverable in different lengths

We also offer the assembly of this conductor as well as the complete cable ready-for-connection in small quantities. Please contact us for any information. We would be glad to submit you our offer without any obligation.

This cable fits for the following headers:

SM08B-SHLS-TF(LF)(SN) (JST), P24021P8 (STM), H113K-D08N-01 / Crimpkontakt M001N-X08N-00R (Entry)

It supports the following LCD's:

TX23D86VM0BAA, TCG101WXLPAANN, TCG121WXLPAANN-AN20, TCG101WXLPAANN-AN20, TCG101WXLPAANN-AN20, TM101JDHG30-00, FX1001P1DSSWMG01.

**BILDER**

