

DATENBLATT

KAB-USB-A-USB-B-MINI-90-LINKS-0500RK



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

BESCHREIBUNG

USB 2.0-1.1 connecting cable USB connector type A and USB-Mini connector type B for mobile hard disks, navigation systems, cockpits and digital cameras.

The special feature of this cable is an angled USB-Mini connector type B. This cable is space saving as to its mounting into housings. Due to its length of only 50 cm there is no additional power supply needed. The cable design is extremely short and thus ideal for mobile applications and for a connection of high-powered USB devices. The twin shielding makes this cable perfectly suitable for industrial applications.

TECHNICAL SPECIFICATIONS:

- side 1: USB-A connector, 180°
- side 2: USB-B-Mini (5-pin) 90° angled to the left in plug direction
- USB wire AWG28/1P (pair twisted data cable), black, l = 500 mm, twin shielding (screen and netting)
- UL2725, temperature class 80°C, voltage class 30V
- operating temperature: -10 °C to 80 °C
- weight: 28.5 g

Further designs are available upon request on short call:

- USB-connector A angulated to the right
- USB connector A angulated to the left
- USB-connector A angulated downwards
- USB-connector A angulated upwards
- USB-connector B angulated to the right
- USB-connector B angulated to the left
- USB-connector B angulated downwards
- USB A + B angulated to the right
- USB A + B angulated to the left
- A angulated to the right + B angulated to the left

ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support

BILDER



ES&S Solutions GmbH
Gewerbering 2
41751 Viersen, Germany

Telefon: +49 (0)2162-266-18-0
Fax: +49 (0)2162-266-18-88
E-Mail: info@esskabel.de

www.esskabel.de

Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support