

DATENBLATT

KAB-USB-B-F-USB-B-M-0300RK



BESCHREIBUNG

USB extension cable type B female with flange for panel mounting and UNC4/40 thread to type B male.

TECHNICAL SPECIFICATIONS:

- side 1: USB type B female with flange, **UNC4/40** thread
- side 2: USB type B male
- USB 1.1 and USB 2.0 compatible
- up to 480 MBit/s
- double shielded, twisted pair
- round cable 28 AWG/1P, 24 AWG/2C, black
- l = 300 mm
- RoHS-compliant
- [UL 2725](#)
- weight: 32 g

This cable is also in 500 mm available.

Please let us know your special requirements as to the USB cable. We would be glad to also offer you customized solutions.

BILDER



Disclaimer: In the absence of confirmation by device specification sheets, ES&S Solutions GmbH takes no responsibility for any defects that occur in equipment using any of ES&S's devices, shown in catalogs, data books, etc. Contact ES&S in order to obtain the latest device specification sheets before using any ES&S's device. ES&S reserves the right to make changes in the specifications, characteristics, data, materials, structures and other contents described herein at any time without notice in order to improve design or reliability. Contact ES&S in order to obtain the latest specification sheets before using any ES&S's device. Manufacturing locations are also subject to change without notice. Observe the following points when using any device in this publication. ES&S takes no responsibility for damage caused by improper use of the devices. ES&S's devices shall not be used for equipment that requires extremely high level of reliability, such as: -Military and space applications -Nuclear power control equipment -Medical equipment for life support