



NOTE: All relevant materials are complied with RoHS directive .



9735-1				
P1		P2		
1	—————	1	RED	24#
2	~~~~~	2	WHITE	
3	~~~~~	3	GREEN	
4	—————	4	BLACK	24#
SHIELD	—————	SHIELD		

7	MOLDED PVC BLACK	H1BF01-0304K09		M304	
6	BLACK HEAT SHRINK RUBE ϕ 1.0*8mm	A4HA64-0959	1	M959	
	MOLDED PE COLOR TRANSPARENT	A5BA02-0280		M280	
	MOLDED PVC BLACK	H1BF01-0304K09		M304	
5	USB 2.0 CABLE, UL STYLE 1 TWISTED PAIR 28AWG AND 2C 24AWG, OD 4.5mm, BRAIN 65% JACKET BLACK, DRAWING No. EUAB2801P2402C-015	H5KH03-0304K09	L-20mm	M304	
4	HEX-NUT 5*7.7mm, #4-40	A6BC03-0095	2	M95	
3	SCREW #4-40 5.5*8mm	A6AC01-0095	2	M95	
2	USB A FEMALE 2.0, GOLD PLATING 30u" ON CONTACTS, WHITE INSULATOR, SOLDER TYPE	A1HC07-0108	1	M108	
1	USB A MALE 2.0, GOLD PLATING 30u" ON CONTACTS, WHITE INSULATOR, CRIMP FOUR PIECES TYPE	A1HA23-0454	1set	M454	
No.	DESCRIPTION			Q'TY	Supplier

PART NO. KAB-A-F-USB-A-M-XXXXSW

APPROVED

CHECKED

DRAWING

DATE

13/FEB/15

ITEM NO.



Cable Length Unless Other Spec. Tolerances:

0 ~200mm	±10mm
201~1000mm	±20mm
1001 ~1500mm	±25mm
1501~2100mm	±30mm
2100mm↑	±40mm

UNIT:mm

