



| Description | | dim. | tol. |
|------------------|----|-------|--------|
| Pitch | P | 0.50 | ± 0.05 |
| Span | SP | 29.50 | ± 0.10 |
| Width | W | 30.50 | ± 0.10 |
| Margin | M | 0.50 | ± 0.10 |
| Cable Length | L | 200 | ±3.0 |
| Contact length | S1 | 4 | ± 0.5 |
| | S2 | 4 | ± 0.5 |
| Stiffener length | S3 | 8 | ±1.5 |
| | S4 | 8 | ±1.5 |
| Insert thickness | T | 0.3 | ±0.05 |
| No of ways | N | 60 | - |
| Shield length | SL | 0 | ± 2.0 |

NOTES

side catcher for Hirose FH28 (FH28-60S-0.5SH)
 *
 *
 *
 *
 FFC0.50A60-0192L-4-4-08-08SC-FH28

| REV | DATE | REVISION DESCRIPTION | PATN | DIM | SIZE | DRWG NO | |
|-----|------|----------------------|------|-------|------|---------|-----|
| | | | 7 | MM | A4 | | |
| | | | DRWG | CHECK | APRV | CODE NO | SHT |
| | | | PASS | PASS | PASS | 0 | 1/1 |
| | | | / | / | / | | |