



PIN ASSIGNMENT:

USB3.0 AM	1	2	3	4	5	6	7	7	8	9	64
Micro USB3.0 BM	1	2	3	5	6	7	8	8	9	10	64
	Red	White	Green	Black	Blue	Yellow	GND	GND	Purple	Orange	Braid
		TP			TP				TP		

OPEN/SHORT TEST: 100% TEST.
INSULATION: MIN 5M.

⑦	Iron Screw:4.3*32.3mm,M2,Nickel plated	2PCS
⑥	Copper foil	2PCS
⑤	PE	5g
④	Black 45P PVC	10g
③	Micro USB3.0 BM(Black Insulator,Nickel Plated)	1PCS
②	USB3.0 AM(Blue Insulator,Nickel Plated)	1PCS
①	UL2725 (28#*1P+D+AL+MY)*2C+28#*1P+24#*2C+AL+D+B(16*6/0.12AM) OD=5.5mm Black PVC Jacket.	1PCS
No.	Description	Q'ty

Company	Goods Code	Draw	Date	2020.07.16
ITEM NO.	Drawing Evidence	Check	Date	
Goods NO.		Approval	Date	
Original NO.	Unit(mm)	Audit	Date	



D		
C		
B		
VER.A	REVISE	Date