



KAB-USB-C-F-PM-USB-C-M-0500SW

PIN ASSIGNMENT:

Type CM	Red	Type CF
A4+B4+A9+B9	—————	A4+B4+A9+B9
A7	—X—X—	A7+B7
A6	—X—X—	A6+B6
A3	—X—X—	A3
A2	—X—X—	A2
B10	—X—X—	B10
B11	—X—X—	B11
Shell+A1+B1+A12+B12	—————	A1+B1+A12+B12+Shell Black+D+4D+B
A11	—X—X—	A11
A10	—X—X—	A10
B2	—X—X—	B2
B3	—X—X—	B3
A8	—————	A8
B8	—————	B8
A5	—————	A5
B5	—————	B5

GEN2,MAX 10GB,3A to Cable
OPEN/SHORT TEST: 100% TEST.
INSULATION: MIN 5M.

⑦	Knurled nuts:M3(5.6*5mm)	2PCS
⑥	PE	5g
⑤	Black 35P PVC	10g
④	Black 45P PVC	10g
③	Type CF(Black Insulator,Nickel Plated),16PIN(A7+B7,A6+B6 Short circuit)	1PCS
②	Type CM(Black Insulator,Nickel Plated),16PIN,No Resistance,10NF	1PCS
①	UL2725 (1/0.20B*1P+D+AL+HMI)*4C+1/0.20B*1P+1/0.20B*4C+7/0.20B*2C+F+D+AB16/5/0.08T OD:5.00m Black PVC Jacket.	1PCS
No.	Description	Q'ty

Company	Goods Code	Draw	OYH	
ITEM NO. USB3.1-TYPECMCF-50CM	Drawing Evidence	Check		Date
Goods NO.		Approval		Date
Original NO.	Unit(mm)			Date



D		
C		
B		
VER.A	REVISE	Date