



PIN ASSIGNMENT

P2	P4	P1	P3
1-----	1-----	A4+B4+A9+B9-----	A4+B4+A9+B9
2-----	2-----	A6-----	A6
3-----	3-----	A7-----	A7
4-----	4-----	A5-----	A5
S-----	S-----	B5-----	B5
		A1+B1+A12+B12-----	A1+B1+A12+B12
		S-----	S

8	NUT BLACK PVC 27P MOLDED.	
7	PVC 45P BLACK.	
6	TYPE C 3.1 F BLACK PBT WITH NICKLE PLATED SHELL F/G.	
5	USB2.0 A F BLACK PBT WITH NICKLE PLATED SHELL.	
4	TYPE C 3.1 M BLACK PBT WITH NICKLE PLATED SHELL F/G.	
3	USB2.0 A M WHITE PBT WITH NICKLE PLATED SHELL F/G.	
2	(32#*1P+AE)*2+32#*1P+24#*2C+EAB OD:4.2MM BLACK PVC JACKET UL2725.	
1	28#*1P+24#*2C+EAB OD:4.5MM BLACK PVC JACKET UL2725.	
NO.	Description	P/N

NOTES:
 1. PIN ASSIGNMENT SEE TO WIRE LIST.
 2. ELECTRICAL TEST CONDITION:
 (a). 100% OPEN, SHORT & MISWIRE TEST,
 (b). INSULATOR RESISTANCE: 10 Mohm MIN.
 DC 300V 0.01sec.
 (c). CONTACT RESISTANCE: 3ohm MAX.

DWG NO:	GOODS CODE	Draw	Date
ITEM NO.	DRAWING EVIDENCE	Check	Date
Goods NO.		Approval	Date
Original NO.	Unit(mm)		



D		
C		
B	WAS 800mm	2020/3/10
VER.A	REVISE	Date.